

## H05VVH2-F ECA

PVC cables

Ordinary duty PVC sheathed cable.



### TECHNICAL DATA

Nominal tension	300/500 V
Conditions of employment	Use in domestic premises and offices, for ordinary duty applications and household appliances, including in damp premises; (e.g. vacuum cleaners, washing machines, spin dryers, and refrigerators); use outdoors for temporary periods of short duration.
Type of electrical conductor	Flexible red copper
Type of insulation	TI2 (EN 50363-3)
Type of outer sheath	TM2 (EN 50363-4-1)
Color of the outer sheath	Black, white, grey
Operating temperature	+5° C   +60° C
Short circuit temperature	+150° C on the conductor (max 5 sec.)
Test voltage	2000 V
Cable marking	ELETTROROBRESCIA IEMMEQU <HAR> H05VVH2-F
Minimum radius of curvature	5 time the max outer diameter in mobile laying, 3 times in fixed laying.

### REFERENCES STANDARDS

Main rule	EN 50525-2-11
Conductor	EN 60228; IEC 60228
Self-extinguishing	EN 60332-1-2; IEC 60332-1-2

## DIMENSIONS

Nominal section	Wires max diameter	Conductor diameter	Insulation thickness	Insulation diameter $\pm$ 0,1	Minimum average external diameter	Medium outer diameter $\pm$ 0,2	Electrical resistance 20°C	Approximate weight	CU Factor
(Nxmm <sup>2</sup> )	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	( $\Omega$ /km)	(kg/km)	(kg/km)
2x0,75	0,21	1,05	0,60	N/A	0,80	4,0x6,3	26,0000	41,00	14,4000

## CORES IDENTIFICATION

Cores number	Insulation colour sequence
2	Blue-Brown

Refer to the CEI EN 50565 standard series as a guide to the use of cables with nominal voltage not exceeding 450/750 V (U0/U) and to the CEI 20-92 standard as a guide for the handling and storage of wooden reels for cables electrical.

Elettrobrescia S.r.l. - Via Bulloni 36 - 25050 - Camignone di Passirano (Bs) - Tel, +39 030 6850663 Fax +39 030 6850444 email: [info@elettrobrescia.it](mailto:info@elettrobrescia.it)