

H05VV-F ECA

PVC cables

Ordinary duty PVC sheathed cable.



TECHNICAL DATA

Nominal tension	300/500 V
Conditions of employment	Use in domestic premises and offices, for ordinary duty applications and household appliances, including in damp premises; (e.g. vacuum cleaners, washing machines, spin dryers, and refrigerators); use outdoors for temporary periods of short duration.
Type of electrical conductor	Flexible red copper
Type of insulation	T12 (EN 50363-3)
Type of outer sheath	TM2 (EN 50363-4-1)
Color of the outer sheath	Black, white, grey
Operating temperature	+5° C +60° C
Short circuit temperature	+150° C on the conductor (max 5 sec.)
Test voltage	2000 V
Cable marking	ELETTRO BRESCIA IEMMEQU <HAR> H05VV-F
Minimum radius of curvature	5 times the max outer diameter in mobile installation, 3 times the max outer diameter in fixed installation.

REFERENCES STANDARDS

Main rule	EN 50525-2-11
Conductor	EN 60228; IEC 60228
Self-extinguishing	EN 60332-1-2; IEC 60332-1-2

DIMENSIONS

Nominal section	Wires max diameter	Conductor diameter	Insulation thickness	Diametro isolamento ± 0,1	Minimum average external diameter	Medium outer diameter ± 0,2	Electrical resistance 20°C	Approximate weight	Fattore CU
(Nxmm ²)	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)	(Ω /km)	(kg/km)	(kg/km)
2x0,75	0,21	1,05	0,60	N/A	0,80	6,4	26,0000	59,00	14,4000
2x1,00	0,21	1,21	0,60	N/A	0,80	6,6	19,5000	67,00	19,2000
2x1,50	0,26	1,44	0,70	N/A	0,80	7,6	13,3000	91,00	28,8000
2x2,50	0,26	1,88	0,80	N/A	1,00	9,2	7,9800	139,00	48,0000
2x4,00	0,31	2,44	0,80	N/A	1,10	10,4	4,9500	159,00	76,8000
3G0,75	0,21	1,05	0,60	N/A	0,80	6,7	26,0000	71,00	21,6000
3G1,00	0,21	1,21	0,60	N/A	0,80	7,0	19,5000	83,00	28,8000
3G1,50	0,26	1,44	0,70	N/A	0,90	8,2	13,3000	114,00	43,2000
3G2,50	0,26	1,88	0,80	N/A	1,10	9,9	7,9800	175,00	72,0000
3G4,00	0,31	2,44	0,80	N/A	1,20	11,2	4,9500	244,00	115,2000
4G0,75	0,21	1,05	0,60	N/A	0,80	7,3	26,0000	88,00	28,8000
4G1,00	0,21	1,21	0,60	N/A	0,90	7,8	19,5000	104,00	38,4000
4G1,50	0,26	1,44	0,70	N/A	1,00	9,2	13,3000	146,00	57,6000

CORES IDENTIFICATION

Cores number	Insulation colour sequence
2,00	Blue-Brown
3,00	Yellow/Green-Blue-Brown
4,00	Yellow/Green-Blue-Brown-Black / Yellow/Green-Brown-Black-Grey

Refer to the CEI EN 50565 standard series as a guide to the use of cables with nominal voltage not exceeding 450/750 V (U0/U) and to the CEI 20-92 standard as a guide for the handling and storage of wooden reels for cables electrical.

Elettro Brescia S.p.A. - Via Bulloni 36 - 25050 - Camignone di Passirano (Bs) - Tel, +39 030 6850663 Fax +39 030 6850444 email: info@elettrobrescia.it